


Univers	Professional
Type	Products
Category	Ropes
Subcategory	Low Stretch Ropes




BEAM 11 mm

The BEAM 11 mm rope is designed for rescue professionals. Its diameter provides a solid grip and great strength. The specific rope construction limits compression and low elongation provides superior efficiency and comfort when handling heavy loads. EverFlex technology makes the rope highly flexible, providing excellent handling over time under a variety of conditions. The rope is available in four colors and four lengths.



The standard diameter provides great strength and a solid grip when handling heavy loads.



EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud). It also helps maintain excellent handling over time, as well as optimal performance with devices (pulleys, descenders, mobile fall-arrest devices).

Short Description High-strength, low stretch kernmantle rope with good handling for rescue





Selling Points





- Standard diameter provides a solid grip and great strength when handling heavy loads
- Consistent performance over time:
 - Specific construction (nylon core and polyester sheath) with a weave that limits rope compression under heavy loads
 - EverFlex technology provides great flexibility over time and under a variety of conditions (water, dust, mud), maintaining excellent handling and optimal performance with devices
 - Low elongation provides superior efficiency and comfort when handling heavy loads
- Available in four colors for easier identification of different kits (white, yellow, blue and red)
- Standard lengths: 200, 300, 600, and 1200 feet





Specification


- Diameter: 11,3mm
- Material(s): Polyester, nylon
- Certification(s): CE EN 1891 type A, NFPA 2500 General Use, Cordage Institute 1801 Low Stretch, XF 494
- Weight per meter: 90g
- Strength: 40kN
- Strength tied with figure-eight knot: 20kN
- Impact force (factor 0,3): 5,9kN
- Number of factor 1 falls: > 20
- Construction: 32 carrier
- Percentage of sheath: 36%
- Static elongation: 2,5%

Specifications by reference

Reference(s)	R101CA00	R101CA01	R101CA02	R101CA03
				
Length (ft)	200 ft	200 ft	200 ft	200 ft
Length	61 m	61 m	61 m	61 m
Color(s)	White	Yellow	Blue	Red
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540848870	3342540848894	3342540848900	3342540848917

Reference(s)	R101CA04	R101CA05	R101CA06	R101CA07
				
Length (ft)	300 ft	300 ft	300 ft	300 ft
Length	92 m	92 m	92 m	92 m
Color(s)	White	Yellow	Blue	Red
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540848283	3342540848290	3342540848306	3342540848313

Reference(s)	R101CA08	R101CA09	R101CA10	R101CA11
				
Length (ft)	600 ft	600 ft	600 ft	600 ft
Length	183 m	183 m	183 m	183 m
Color(s)	White	Yellow	Blue	Red
Made in	CZ	CZ	CZ	CZ
Guarantee	3 years	3 years	3 years	3 years
Inner Pack Count	1	1	1	1
Quantity Per Box	1	1	1	1
EAN	3342540848160	3342540848177	3342540848184	3342540848191

Reference(s)	R101CA12
	
Length (ft)	1200 ft
Length	366 m
Color(s)	White
Made in	CZ
Guarantee	3 years

Inner Pack Count	1
Quantity Per Box	1
EAN	3342540848320

Accessory(ies) PROTEC
 PROTEC PLUS
 ROLLER COASTER
 Rope end identification kit

Related product(s) I'D® S
 MAESTRO® S
 RESCUCENDER
 ROLLCLIP A
 SPIN L1
 SPIN L2
 SPIN L1D
 BUCKET 45
 ASAP®
 ASAP® LOCK